



PRODUCT DATA SHEET

Monarflex Extreme T Plus FireSmart

High Strength Scaffold Sheeting

A high strength reinforced low density polyethylene with flame retardant formulation.

- Patented eyelet design
- Unique high performance Anchor & Strap fixing system
- Suitable for screen printing

TECHNICAL DETAILS	
Material	Reinforced Low Density Polyethylene (LDPE)
Roll Size	2m x 45m
Colour	White
Grid	8mm x 8mm PET MUJ 1670 dtex
Thickness	0.2mm
Roll Weight	27kg
Tensile Strength	18kN/m (MD) 16.5kN/m (TD)
Eyelet Pullout	957N
Eyelets Per Roll	270
Light Transmission	50%
Conforms to	BS 7955, BS 8093 CP for use of scaffold sheets
Fire Protection	LPS 1207, LPS 1215
Application	Internal and external use



ECS House,
Willsborough Industrial Estate,
Clonshaugh, Dublin 17.
Tel: 01 802 3333
Fax: 01 803 6060
Email: necoflexsupport@icopal.com
Website: www.necoflex.ie

NOTE: This information is given in good faith being based on the latest knowledge known to Necoflex Ltd. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume; based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.