



## PRODUCT DATA SHEET

# Monarflex Extreme T Plus

## High Strength Scaffold Sheeting

High strength reinforced low density polyethylene.

- Patented eyelet design
- Unique high performance Anchor & Strap fixing system
- Suitable for screen printing
- Available in flame retardant version

TECHNICAL DETAILS	
Material	High strength reinforced Low Density Polyethylene (LDPE)
Roll Size / Weight	2m x 45m (24kg)
Colour	Clear
Grid	8mm x 8mm PET MUJ 1670 dtex
Thickness	0.2mm
Tensile Strength	18kN/m (MD) 16.5kN/m (TD)
Eyelet Pullout	950N
Eyelets per Roll	270
Light Transmission	>80%
Conforms to	BS 7955, BS 8093 CP for use of scaffold sheets



ECS House  
Willsborough Industrial Estate,  
Clonshaugh, Dublin 17  
Tel: 01 802 3333  
Fax: 01 802 6060  
Email: [necoflexsupport@icopal.com](mailto:necoflexsupport@icopal.com)  
Website: [www.necoflex.ie](http://www.necoflex.ie)

NOTE: This information is given in good faith being based on the latest knowledge known to Necoflex Ltd.

Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume; based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.