



PRODUCT DATA SHEET

Monarflex Scaffband Flamesafe

Scaffold Sheeting

An economy sheeting recommended for use in low rise, shorter term projects that are not exposed to high wind risk.

- Choice of high performance Flexities or Euroties fixing systems
- Lightweight for easy handling on site and suitable for DigiWrap printing

TECHNICAL DETAILS	
Material	Reinforced Low Density Polyethylene (LDPE)
Roll Size / Weight	2m x 45m (18kg) +/- 5% 3m x 45m (27kg) +/- 5%
Colour	White
Grid	HDPE/PP fibrillated tape in an 8mm X 8mm grid
Thickness	0.2mm (film 98 micron)
Light Transmission	>38%
Tensile strength	700N (elongation 20%) +/- 10 %
Tearing strength	80N +/- 10%
Thermal stability	- 40C to + 80 C
Eyelets	At 100mm centres on three reinforced bands of 7cm positioned horizontally along the width of the sheet
F R	According to EN 13501-1 Class B (LPS 1215)
Conforms to	BS 7955, BS 8093 CP for use of scaffold sheets
Use	External only

NOTE: This information is given in good faith being based on the latest knowledge known to Necoflex Ltd. Whilst every effort has been made to ensure the contents of the publication are current while going to press, customers are advised that products, techniques and Codes of Practice are under constant review and liable to change without notice. Up to date information is available from our Technical Services Department on request.

Responsibility cannot be accepted for the application of products, and no claims can be considered, where the manufacturer's instructions have not been followed. The user should not assume; based on information provided in this sheet, that the product is suitable for any abnormal use.

All products are sold subject to our standard conditions of sale, available on request.



ECS House,
Willsborough Industrial Estate,
Clonsaugh, Dublin 17
Tel: 01 802 3333
Fax: 01 803 6060
Email: necoflexsupport@icopal.com
Website: www.necoflex.ie